

Appl. No. 10/604,722  
Amdt. dated August 15, 2005  
Reply to Office action of 06/30/2005

**Amendments to the Claims:**

This listing of claims replaces all previous versions and listings of claims in the application:

**Listing of Claims:**

1 (currently amended): An image projection system comprising:

- 5       a light source for generating a light beam;  
      a reflective housing comprising an opening, the opening having a diameter smaller  
      than a maximum diameter of the reflective housing, the reflective housing  
      forming an accommodating space, the light source installed inside the  
      accommodating space so that the light beam generated by the light source  
10       substantially propagates along an optical path through the opening away from  
      the accommodating space, wherein the reflective housing is substantially  
      parabolic shaped, and the optical path is a substantially parallel route by which  
      the light beam propagates after being reflected by the parabolic reflective  
      housing; and  
15       an invisible-light reflector installed at a reflecting position intersecting with the  
      optical path outside the opening of the reflective housing, a normal of the  
      invisible-light reflector and the optical path intersecting to form a predetermined  
      angle so that invisible light of the light beam emitted from the opening will be  
      reflected back into the accommodating space;  
20       wherein the predetermined angle formed by the normal of the invisible-light  
      reflector and the optical path is an acute angle not equal to zero degrees, so that  
      infrared rays of the light beam reflected back into the accommodating space by the  
      invisible-light reflector will not focus on the reflective housing.
- 25   2 (previously presented): The image projection system of claim 1, wherein the reflective  
      housing comprises an elliptic reflective housing, and the light source is installed at a

Appl. No. 10/604,722  
Amdt. dated August 15, 2005  
Reply to Office action of 06/30/2005

focal point of the elliptic reflective housing, and the optical path is a major axis of the elliptic reflective housing.

3 (cancelled)

5

4 (previously presented): The image projection system of claim 1, wherein the image projection system further comprising a light tube connected to the light source, wherein the infrared rays of the light beam reflected back into the accommodating space by the invisible-light reflector will not focus on the light tube.

10

5 (previously presented): The image projection system of claim 1, wherein the acute angle is smaller than 45 degrees.

15

6 (previously presented): The image projection system of claim 1, wherein the image projection system further comprises an image module, the image module comprising a plurality of controllable optical reflectors for modulating the light beam passing through the invisible-light reflector to generate a projecting beam containing an optical image, wherein the light beam passing through the invisible-light reflector does not comprise the infrared rays.

20

7 (previously presented): The image projection system of claim 6, wherein the image module is a digital micro-mirror device.

8-16 (cancelled).

25

17 (previously presented): The image projection system of claim 1, further comprising an image module, wherein the image module is a liquid crystal panel.

Appl. No. 10/604,722  
Amdt. dated August 15, 2005  
Reply to Office action of 06/30/2005

18 (previously presented): The image projection system of claim 1, wherein the invisible-light reflector is immediately adjacent to the reflective housing along the optical path.

5 19 (cancelled).

20 (previously presented): An image projection system comprising:

a light source for generating a light beam;

10 a parabolic reflective housing comprising an opening, the parabolic reflective housing forming an accommodating space, the light source installed inside the accommodating space so that the light beam generated by the light source substantially propagates along an optical path through the opening away from the accommodating space; and

15 an invisible-light reflector installed at a reflecting position intersecting with the optical path outside the opening of the parabolic reflective housing, a normal of the invisible-light reflector and the optical path intersecting to form a predetermined angle so that invisible light of the light beam emitted from the opening will be reflected back into the accommodating space;

20 wherein the predetermined angle formed by the normal of the invisible-light reflector and the optical path is an acute angle not equal to zero degrees, so that infrared rays of the light beam reflected back into the accommodating space by the invisible-light reflector will not focus on the parabolic reflective housing.

21 (previously presented): The image projection system of claim 20, wherein the optical  
25 path is a parallel route by which the light beam propagates after being reflected by the parabolic reflective housing.